

TEMPO





Use: garden - terrace - balcony - pool area



Fibres height: ± 35 mm
Total height: ± 37 mm




CLOSE TO REALITY
SOFTNESS
TRAMPLING RESISTANCE

CHARACTERISTICS
Fibres composition: 62% PE / 38% PP
Fibres weight: 925 g / m² \pm 10%
Total weight: 1585 g / m² \pm 10%
Dtex : 5850
Straight fibres  
Curly fibres  
Gauge : 5/16"
Stitches number/ 10 cm: 15 \pm 10%
Loops number: 18900 / m² \pm 10%
Primary backing: PP 90 g / m²
Secondary backing: LATEX 570 g / m²

REFERENCES AND EAN CODES
2 m x 25 m GTE35C2 / 3700379025280
4 m x 25 m GTE35C4 / 3700379025297
<i>Cut-to-size available</i>
2 m x \curvearrowright CTE35C2 / 3700379025402
4 m x \curvearrowright CTE35C4 / 3700379025419

IMPORTANT

As colour might slightly vary from batch to batch, batches must not be mixed.

Sommer Flooring Ltd

22 Spitfire Close

Coventry – CV5 6UR

www.sommerltd.com

Tel : 024 7798 1711

E-mail : info@sommerltd.com

